



Techron[®] Concentrate Plus

Ultra high performance gasoline fuel system cleaner

Product description

Techron Concentrate Plus is an ultra high performance gasoline fuel system cleaner. Formulated with Chevron's advanced polyether amine (PEA) technology, it offers complete fuel system treatment in gasoline passenger cars, vans and light trucks.

Techron Concentrate Plus is designed to aid the removal of harmful deposits from fuel injectors, carburetors, inlet valves and combustion chambers in a wide range of gasoline engines, including port fuel injection (PFI), direct fuel injection (DISI), hybrids and flex-fuel engines. Techron Concentrate Plus is compatible and protective in many commercially available ethanol blends such as E10 and E85 fuels.

Customer benefits

One tank of gasoline fuel treated with Techron Concentrate Plus offers:

- Improved fuel economy by aiding the removal of harmful fuel injector and intake valve deposits
- Restored engine power, acceleration and performance
- Better cold start performance
- Reduced deposit-related knock and ping
- A reduction in harmful exhaust emissions

Product highlights

- **Fuel economy performance**
- **Engine power and acceleration**
- **Cold start performance**
- **Deposit-related knock and ping protection**
- **Exhaust emissions reduction**

Applications

Techron Concentrate Plus is designed for:

- Spark ignition four-stroke engines fuelled by gasoline, ethanol, gasoline/ethanol blends in passenger cars, vans and light trucks
- Gasoline hybrid vehicles
- Four-stroke outboard motors
- 2-stroke engines

Techron Concentrate Plus is not recommended for:

- Diesel engines
- Aviation use

Techron Concentrate Plus:

- Is compatible with many commercially available ethanol blends
- Does not contain sulphur
- Will not harm catalytic converters and oxygen sensors
- Will not contribute to engine crankcase sludge

Approvals, performance and recommendations

Recommendations

- Techron Concentrate Plus is recommended by major automakers.

Treatment level

- Add one 350 ml bottle of Techron Concentrate Plus to one tank (50-70 litres) of gasoline every 8,000 to 16,000 kilometers or at scheduled oil change intervals; not to exceed twice per oil change.

Note: Always confirm that the product selected is consistent with the original equipment manufacturers recommendation for the equipment operating conditions and customer's maintenance practices.

Typical test data

Test	Test methods	Results
Shelf Life: 60 months from date of filling indicated on the product		
Appearance	Visual	Clear, bright liquid
Kinematic Viscosity at 40°C, mm ² /s	ASTM D445	3.53
Relative density at 15°C	ASTM D1298	0.865
Flash Point, PM, °C	ASTM D93	79

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheets.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product